Panasonic



TOUGHBOOK A3

- TOUGHBOOK A3's eco-system of software, services and partners powered by productivity+
- Optional 1D/2D barcode reader, Insertable SmartCard or 2nd USB Type-A
- Five user-defined buttons from maximum user functionally
- Dual hot swap battery design
- Certified to latest MIL-STD-810H standards
- FirstNet Ready[™] and supports Band 14 connectivity
- 3 Year limited warranty, parts and labor







OUR MOST POWERFUL ANDROID TABLET OFFERING YET. FEATURING LONG-LIFE SUPPORT FOR MISSION-CRITICAL ENTERPRISE APPLICATIONS.

The Panasonic TOUGHBOOK A3 is a rugged Android™ 10.1" tablet that is the latest addition to our rugged lineup. The TOUGHBOOK A3 has a powerful octa-core processor, supports 4G LTE and FirstNet® connectivity and an insertable stylus. The tablet has the flexibility to be used in all markets including warehousing, logistics and transportation. Equipped with an optional integrated barcode reader and insertable smart card reader the TOUGHBOOK A3 is also ideal for enterprise retail and federal markets. The TOUGHBOOK A3 also features a 10.1" outdoor-viewable display with rain and glove touch functionality making this tablet the choice for outdoor workers everywhere. Featuring a 6 foot drop rating and IP65 certification for dust and water resistance the TOUGHBOOK A3 is purpose built to get more out your day.





TOUGHBOOK A3

DUDABULTY

DURABILITY	 MIL-STD-810H certified¹6 IP65 dust and water resistant 6' drop-resistant and tumble tested (500 tumbles, 3.3ft. 5 rpm)
SOFTWARE	■ Android 9.0 [Pie] ¹⁷
CPU	■ Qualcomm® SDM660 2.2GHz/1.843GHz Octa-core
STORAGE & MEMORY	 Memory: 4GB [LPDDR4]¹ Storage eMMC: 64GB¹ Additional storage available with optional Storage Card: SD (up to 2 GB), SDHC (up to 32 GB), SDXC (up to 64 GB)²
DISPLAY	 10.1" WUXGA 1920 x 1200 10-point capacitive multi touch with rain sensing and glove touch modes Display with direct bonding Automatic screen rotation Anti-reflective (AR) screen treatment 500nit typical (800nit max)
AUDIO	■ Integrated microphone ■ Loud Speaker 94dBA
KEYBOARD & INPUT	 10-point gloved multi touch 5 user definable buttons On-screen QWERTY keyboard
SENSORS	Ambient light / Proximity / Digital Compass / Gyro / Acceleration
CAMERAS	8MP rear camera with LED flash 5MP front facing camera
EXPANSION	■ microSDXC (up to 64 GB)²
INTERFACE	Docking connector USB 3.0 Type-C® host³ (OTG, BC1.2) USB Type-A host Mini-jack stereo headphone & microphone
WIRELESS	 Qualcomm® WCN3990 IEEE802.11 a/b/g/n/ac/d/h/i/r/k/v/w with MIMO Optional Sierra Wireless AirPrime® EM7511 - 4G LTE and HSPA+ Certified with Verizon, AT&T and FirstNet™ Nano SIM card slot (x2) Bluetooth® V5.0 Class1 GPS GPS/GL0NASS/Galileo/Beidou/QZSS Near Field Communication [NFC - Type A, Type B, FeliCa
POWER SUPPLY4.5.6.7.8.9.10.11	Dual standard batteries: Li-lon 3.8V, 3,200mAh Dual standard battery operation Approx. 9 hours based on standard enterprise user profile Hot Swap with clock backup Standard battery charging time: Power on or off approx. 4 hours Available with dual extended life batteries: Li-lon 3.8V, 5,580mAh Dual extended battery operation Approx. 15.5 hours based on standard enterprise user profile Extended battery charging time: Power on or off approx. 6.5 hours USB Type-C® charging capacity sold separately
POWER MANAGEMENT ¹¹	■ Consumption approx, 32W ^{12,13}
SECURITY FEATURES	 ARM® TrustZone® [Built-in] NFC Smart Card Reader (optional) Kensington lock
WARRANTY	■ 3 year limited warranty, parts and labor
DIMENSIONS & WEIGHT ^{14,15}	 10.7" x 7.72" x 0.65" (without barcode reader section) Approx. 1.98 lb. with dual batteries

INTEGRATED OPTIONS

- 4G LTE Band 14 EM7511 multi carrier mobile broadband with satellite GPS
 Choice of 1D/2D barcode reader (SE4750) with LED light, Insertable Smart Card or 2nd USB Type-A. Combinations vary by SKU configuration.

ACCESSURIES	
 Single Bay Desktop USB and Ethernet I/O Cradle 	FZ-VEBA21U
 AC Adapter with AC Cord 	CF-AA6413AM
 5-Bay Battery Charger with 100W Power Supply 	FZ-VCBT131M
and AC Cord	
 Standard Battery 3,200mAh 	FZ-VZSUT10U
 Extended Battery 5,580mAh 	FZ-VZSUT11U
 Rotating Hand Strap (All Configurations) 	FZ-VSTA31U
Pen Tether with Stylus Loop	CF-VNT002U
■ Passive Stylus Pen	CF-VNP025U
■ Shoulder Śtrap	CF-VNS331U
Screen Protector Film	FZ-VPFA31U

Please consult your reseller or Panasonic representative before purchasing.

Specifications given herein may be changed at any time without prior notice

¹ 1 MB = 1,048,576 bytes, 1 GB = 1,073,741,824 bytes

- One ration has been tested and confirmed using the following Panasonic brand memory cards: SD (up to 2 GB), SDHC (up to 32 GB), SDXC (up to 64 GB). Compatibility with other SD devices is not guaranteed.
- ³ Does not guarantee operation of all USB-compatible peripherals. USB Type-C[®] will charge the device if the input source is 1000mA or higher. If the source is less than 1000mA the device will not charge
- 4 25°C (77°F) environment. Temperature range for charging: 10°C to 35°C (50°F to 95°F) Humidity: 30% to 80% relative humidity.
- $^{\rm 5}$ The AC adaptor is designed for use with power sources that supply up to 240 V AC.
- ⁶ Actual performance varies depending on usage conditions, connected peripherals, etc. Typically, operating time is reduced in colder environments.
- 7 Talk time may vary depending on the condition of the mobile network.
- 8 As defined by the JEITA Specification, Working Mode B. (Two times reading in every 10 seconds)
- Finterprise user profile: Measured with LCD brightness: 150 cd/m2, Web browsing every 20 seconds through WLAN. Battery life varies depending on the usage conditions or when an optional device is attached.
- 10 Charging with optional cradle. Varies depending on usage conditions.
- ¹¹ Hot swap activation is automatic when one battery is removed at a time as long as battery percentage indicator is above 30%. If the battery percentage indicator is below 30% then on screen instructions will require the user to turn off the screen first to maintain hot swap mode. Hot swap mode is deactivated when the battery percentage indicator is at 15%.
- 12 When the battery is fully charged (or not being charged) and the unit is off.
- ¹³ Powered with optional cradle. Rated power consumption
- ¹⁴ Actual size may vary by unit configuration.
- ¹⁵ Average weight. Actual weight may vary by unit configuration.
- ¹⁶ Do not expose the skin to this product when using the product in a hot or cold environment. When using the product in hot or cold environments, some peripherals may not perform properly. Confirm the recommended operation environment of the peripherals. Using the product continuously hot environments will shorten the product life. Avoid continuous use in these types of environments. When using the product in cold environments, the product may take longer to start up and battery operation time may be reduced. Even when using the product within the temperature and humidity ranges listed here, using the product continuously in extreme environments will result in product deterioration and will shorten the life of the product.
- ¹⁷ Product functionality cannot be guaranteed if the operating system is modified or replaced by the user or a third party.

1.800.662.3537

na.panasonic.com/TOUGHBOOKA3

Google, Android, Google Play and other marks are trademarks of Google LLC. Pie is a trademark of Mondelez International, Inc. group. The Android robot is reproduced or modified from work created and shared by Google and used according to terms in the Creative Commons 3.0 Attribution License. FirstNet, First Responder Network Authority, and FirstNet logo are registered trademarks and service marks of the First Responder Network Authority, an independent authority within the U.S. Department of Commerce. All other marks are the property of their respective owners. Panasonic is constantly enhancing product specifications and accessories. Specifications subject to change without notice. Trademarks are property of their respective owners. © 2020 Panasonic Systems Corporation of North America. All rights reserved. TOUGHBOOK A3 Spec Sheet 05/20. PSS-M201455SS







